



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

RPC-3.50 according to	IEC 60169-23
RPC-3.50 mechanically compatible with	RPC-2.92 and SMA
RPC-TNC according to	IEC 61169-26

Documents

N/A

Material and plating

Connector parts

Center contact
Outer contact
Flange
Dielectric 1
Dielectric 2

Material

CuBe
Stainless steel
Brass
PPE
PTFE

Plating

Gold, min. 1.27 µm, over chemical nickel
Passivated
Flash white bronze over silver(e.g. Optargen®)

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

Electrical data

Impedance	50 Ω
Frequency	DC to 18 GHz
Return loss	≥ 35 dB, DC to 2.5 GHz ≥ 25 dB, 2.5 GHz to 6 GHz ≥ 20 dB, 6 GHz to 16 GHz ≥ 17 dB, 16 GHz to 18 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage (at sea level)	1000 V rms
Working voltage (at sea level)	335 V rms

Mechanical data

Mating cycles RPC-3.50	≥ 500
Mating cycles RPC-TNC	≥ 1000
Center contact captivation	≥ 27 N
Coupling test torque RPC-3.50	1.70 Nm
Recommended torque RPC-3.50	0.80 Nm to 1.10 Nm
Misalignment	radial 0.7 mm min
Spring force	min. 33 N at rest Max. 62 N at max. spring travel
Spring travel	7 mm max.

Environmental data

Temperature range	-40°C to +85°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Weight

53.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
H. Babinger	09.08.04	F. Reiner	26.06.18	c01	18-1026	M. Ruf	25.06.18

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2
--	--	--	--	--	--	---------------