



All dimensions are in mm; tolerances acc. to ISO 2768 m-H

Interface

Compatible to MIL-STD-348

Documents

PCB layout B 127
Tape & reel packaging VG05.75000

Material and plating

Connector parts

Center contact
Outer contact
Dielectric

Material

Brass
Brass
LCP

Plating

AuroDur®, gold plated
AuroDur®, gold plated

SMP

Straight Plug PCB
Catchers Mit

19S14K-40ML5

Electrical data

Impedance	50 Ω
Frequency	DC to 26.5 GHz
Return loss	≥ 26 dB @ DC to 6 GHz ≥ 21 dB @ 6 GHz to 12 GHz
Insertion loss	≤ 0.1 x √f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 6 mΩ
Outer contact resistance	≤ 2 mΩ
Test voltage (at sea level)	500 V rms
Working voltage (at sea level)	335 V rms
Contact Current	≤ 1.2A DC

- Connector only, Return loss in application depends decisive on PCB layout -

Mechanical data

Mating cycles	
if mating part is Smooth bore, Catcher's Mitt	≥ 1000
Center contact captivation	≥ 7 N
Engagement force	
- Smooth bore, Catcher's Mitt	≤ 9 N
Disengagement force	
- Smooth bore, Catcher's Mitt	≥ 2.2 N

Environmental data

Temperature range	-65 °C to +155 °C
Rapid change of temperature	IEC 60068-2-14 (-65 °C to 155 °C, 1h dwell, 50 cycles)
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition A
Damp heat	IEC 60068-2-78 (40°C, 93% RH, 56d)
High temperature endurance	IEC 61169-1, Sub-clause 9.6 (+155 °C, 1000 hours)
Max. soldering temperature	IEC 61760-1, +260 °C for 10 sec.
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Weight

Weight 0.7 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Schmid	30/06/08	Chr. Janßen	28.10.20	f00	20-1927	S. Huber-Siegl	28.10.20
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2