



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 61169-36

Documents

N/A

Material and plating

Connector parts

Center conductor
Outer conductor
Dielectric
Substrate

Material

Brass
Beryllium copper
PTFE, Silicone
Al₂O₃

Plating

Gold, min. 1.27 µm, over nickel
Gold, min. 0.8 µm, over nickel

Technical Data Sheet**Rosenberger**

MCX

Termination
Plug 1 Watt**29S15R-1.0E3****Electrical data**

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 23.1 dB, DC to 4 GHz ≥ 17.7 dB, 4 GHz to 6 GHz
Power handling (at 25 °C, sea level)	1 W at 2.5 GHz, derated linearity by 0.01 W/K

Mechanical data

Mating cycles	≥ 500
Center contact captivation	≥ 10 N
Engagement force	≤ 25 N
Disengagement force	8 N to 20 N

Environmental data

Temperature range	-55 °C to +155 °C
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Packing

Standard	100 pcs in bag
Weight	0.7 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	16.02.05	Markus Müller	22.05.18	b00	18-1027	Marion Striegler	22.05.18
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2