



chain of balls stretched length with loop 82mm

All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-16, MIL-PRF-39012, CECC 22210

Documents

N/A

Material and plating

Connector parts

- Cover plate
- Rivet
- Chain of balls
- Loop
- Gasket

Material

- Brass
- Brass
- Brass
- Brass
- Kautex

Plating

- White bronze(e.g. Optalloy®)
- White bronze(e.g. Optalloy®)
- White bronze(e.g. Optalloy®)
- White bronze(e.g. Optalloy®)

Electrical data

N/A

Mechanical data

Mating cycles min. 500
Coupling nut retention ≥ 450 N
Coupling test torque max. 1.7 Nm
Recommended torque 0.7 Nm to 1.1 Nm

Environmental data

Temperature range -55°C to +155°C
Thermal shock MIL-STD-202, Meth. 107, Cond. B
Corrosion MIL-STD-202, Meth. 101, Cond. B
Vibration MIL-STD-202, Meth. 204, Cond. B
Shock MIL-STD-202, Meth. 213, Cond. I
Moisture resistance MIL-STD-202, Meth. 106
Degree of protection (mated pair) IEC 60529, IP68
RoHS compliant

Tooling

N/A

Suitable cables

N/A

Weight

Weight 10.6 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	22/06/04	J_Gramsamer	16.04.15	d00	15-0397	J_Krautenb.	16.04.15
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel.: +49 8684 18-0 email: info@rosenberger.de			Page 2 / 2