



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface
According to DIN 72594-1

Documents
Assembly instruction MA_59V065

Material and plating

Connector parts

- Center contact
- Center contact 2
- Outer contact
- Body
- Dielectric
- Crimping ferrule
- Cover

Material

- Spring bronze
- Brass
- Spring bronze
- Brass
- LCP
- Copper
- Alpaca

Plating

- Gold, min. 0.8 µm, over chemical nickel
- Gold, min. 0.15 µm, over chemical nickel
- Nickel, 2.5-5 µm
- Nickel, 2.5-5 µm

FAKRA - HF RIGHT ANGLE JACK
360°

59K25H-106A4

Electrical data

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 26 dB, DC to 1 GHz ≥ 24 dB, DC to 3 GHz ≥ 17 dB, DC to 6 GHz
Insertion loss	≤ 0.1 $\sqrt{f(\text{GHz})}$ dB @ 1 GHz
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 15 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
RF-leakage	≥ 65 dB up to 1 GHz

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 6.2
Temperature and humidity	DIN 72594-2 clause 6.3
Vibration and mechanical shock	DIN 72594-2 clause 6.1
Dry heat	DIN 72594-2 clause 6.4
2002/95/EC (RoHS)	compliant

- Limitations are possible due to the used cable type -

Tooling

Crimping tool	11W150-000
Crimp insert	11W150-508

Suitable cables

Cable type	RG 58
------------	-------

Packing

Standard	1.000 pcs in box
Weight	4.43 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Wolfgang Lankes	15/02/07	Wolfgang Lankes	18/03/08	b00	08-0197	Inge Mühlauer	17/03/08
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2