



**Electrical data**

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss measured on 50W footprint	≥ 24 dB (DC to 2.4 GHz) ≥ 16 dB (2.4GHz to 4 GHz)
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 <sup>3</sup> MΩ
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
<i>- Connector only, VSWR in application depends decisive on PCB layout</i>	

**Mechanical data**

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N
Retention force plastic housing	≥ 110 N
Coding efficiency	≥ 40 N

**Environmental data**

Temperature range	-40 °C to 105 °C
Thermal shock	DIN 72594-2 clause 6.2
Temperature and humidity	DIN 72594-2 clause 6.3
Vibration and mechanical shock	DIN 72594-2 clause 6.1
Dry heat	DIN 72594-2 clause 6.4
Soldering profile 2002/95/EC (RoHS)	acc. IEC 60068-2-58 group 3&4 compliant

**Tooling**

N/A












**Packing**

Standard	50 pcs. in blister tray, 200 pcs. on tape and reel
Weight	9.8 g

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2

**Coding**

Coding	Color	RAL	Part-Number
 A	black	sim. 9005	59S2AA-400A5-A
 B	white	sim. 9001	59S2AA-400A5-B
 C	blue	sim. 5005	59S2AA-400A5-C
 D	claret violet	sim. 4004	59S2AA-400A5-D <sup>(k)</sup>
 E	green	sim. 6002	59S2AA-400A5-E
 F	brown	sim. 8011	59S2AA-400A5-F
 G	grey	sim. 7031	59S2AA-400A5-G
 H	violet	sim. 4003	59S2AA-400A5-H
 I	beige	sim. 1001	59S2AA-400A5-I
 K	curry	sim. 1027	59S2AA-400A5-K
 Z	waterblue	sim. 5021	59S2AA-400A5-Z

**Change History**

Rev.	Date	Change
k00	06.08.2019	- added quality inspection marking - renamed color of D-Coding, color stays the same
j00	19.06.2018	- changed tolerance dimension - additional dimension feet length

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Thomas Höfling	13.06.07	C.Düh	06.08.19	k00	19-1424	J. Frey	06.08.19