



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 61169-4, EN 122190, DIN 47223

Documents

N/A

Material and plating

Connector parts

- Center contact
- Outer contact
- Coupling nut
- Heatsink
- Dielectric
- Substrate

Material

- Brass
- Brass
- Brass
- Aluminum
- PPE
- AlN

Plating

- Silver, 3-6 μ m
- Flash white bronze over silver(e.g. Optargen®)
- White bronze(e.g. Optalloy®)
- Black anodized

Technical Data Sheet

Rosenberger

7-16

Termination
Plug 5 Watt

60S17R-005N1

Electrical data

Impedance	50 Ω
Frequency	DC to 8 GHz
Return loss	≥ 34.1 dB, DC to 1 GHz ≥ 30.7 dB, 1 GHz to 2 GHz ≥ 20.0 dB, 2 GHz to 8 GHz
Power handling (at 25 °C, sea level)	≤ 5 W, derated linearity by 0.05 W/K

Mechanical data

Mating cycles	≥ 500
Coupling nut retention	≥ 1000 N
Center contact captivation	≥ 200 N
Coupling torque (recommended)	25 to 30 Nm
Proof torque	≤ 35 Nm

Environmental data

Temperature range	-65 °C to +85 °C
RoHS	compliant

Tooling

N/A

Suitable cables

N/A

Packing

Standard	1 pce in bag
Weight	149 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	26.05.05	Markus Müller	20.07.18	c00	18-1027	Marion Striegler	20.07.18
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de			Page 2 / 2