



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 61169-54

**Documents**

Assembly instruction 1D7-C06

**Material and Plating**

**Connector parts**

Center contact	<b>Material</b> CuBe	<b>Plating</b> Silver, 3-6 µm
Outer contact	Brass	Silver, 3-6 µm
Body	Brass	White bronze(e.g. Optalloy®)
Back nut	Brass	Nickel, 2.5-5 µm
Dielectric	PTFE and TPX	
Gasket	Silicone & EPDM	
Spring part	Spring bronze	Tin, 1-3 µm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RFB00035/12.20/6.4

**Electrical Data**

Impedance	50 Ω
Frequency	DC to 12 GHz
Return loss	≥ 36 dB @ DC to 2.7GHz
Insertion loss	≤ 0.05 x √ f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 1.0 mΩ
Outer contact resistance	≤ 1.0 mΩ
Test voltage	2500 V rms
Working voltage	500 V rms
RF-leakage	≥ 110 dB @ DC to 6 GHz ≥ 90 dB @ DC to 3 GHz for tool-less plugs ≥ 70 dB @ 3 to 6 GHz for tool-less plugs
Power handling (at 90 °C, altitude 3000m)	500 W @ 2.0 GHz
Intermodulation (3 <sup>rd</sup> order)	≥ 160 dBc (2 x 46 dBm) @ 0.4 – 4.0 GHz ≥ 166 dBc (2 x 43 dBm) @ 0.4 – 4.0 GHz

- Limitations are possible due to the used cable type -

**Mechanical Data**

Mating cycles	≥ 100
Recommended torque	5 Nm

**Environmental Data**

Temperature range	-55 °C to +90 °C operating temperature
Thermal shock	IEC 61169-1 9.4.4
Corrosion resistance	ISO 21207 method B
Vibration	IEC 61169-1 9.3.3 and IEC 60068-2-64
Shock	IEC 61169-1 9.3.14
Degree of protection (mated pair)	IEC 60529, IP68 1 h / 25 m
RoHS	compliant

**Tooling**

Stripping tool	SLT001-C06, 60W110-C06
----------------	------------------------

**Suitable Cables**

SL 114R Series (recommended) and similar

**Weight**

286 g/pc

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
F. Fraunhofer	22.10.2015	Chr. Janßen	04.03.2021	b00	20-1927	B. Wollitzer	04.03.2021
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.com">www.rosenberger.com</a>					Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.com">info@rosenberger.com</a>		Page 2 / 2