



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Description**

Protection cap for 4.1-9.5 and 4.3-10 female connectors.

**Material and plating**

**Connector parts**

Protection Cap  
Gasket

**Material**

Brass  
PVC

**Plating**

White bronze(e.g. Optalloy®)

**Mechanical data**

Torque (recommended) 10 to 15 Nm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

4.1-9.5 /  
4.3-10

Protection Cap with cord

**65Z001-001N**

**Environmental data**

Temperature range	-55°C to +155°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106
Degree of protection (mated pair)	IEC 60529, IP68
RoHS	compliant

**Weight**

Weight	11.7 g/pce
--------	------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
J. Gramsamer	05/11/14	J. Gramsamer	12.11.14	100	14-v660	S. Huber-Siegl	12.11.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>						Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>	
							Page
							2 / 2