

All dimensions are in mm

**Interface**

According to RN\_108-04

**Documents**

Assembly instruction MA\_AMV003

**Material and plating**

**Connector parts**

- Center contact
- Interface
- Crimp area
- Outer contact (Contact part)
- Outer contact (Crimp part)
- Dielectric
- Crimping sleeve
- Housing
- Secondary lock

**Material**

- Spring bronze
- Spring bronze
- Stainless steel
- PA12-GB30
- Spring bronze
- PBT-GF20
- PBT-GF20

**Plating**

- Gold, min. 0.15 µm, over chemical nickel
- Tin, min. 1 µm, over chemical nickel
- Tin, 1.5-3 µm
- Tin, 1.5-3 µm
- Tin, 1.5-3 µm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2

**Electrical data**

Impedance	50 Ω
Frequency	DC to 15 GHz
Return loss	≥ 25 dB, DC to ≤ 3 GHz ≥ 20 dB, > 3 GHz to ≤ 6 GHz ≥ 15 dB, > 6 GHz to ≤ 12 GHz ≥ 12 dB, > 12 GHz to ≤ 15 GHz
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 <sup>3</sup> MΩ
Center contact resistance	≤ 15 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	≤ 800 V rms
Working voltage	≤ 60 V DC
Power current	≤ 1 A DC

- Limitations are possible due to the used cable type -  
- Measurement procedure according to RN\_107-1 -

**Mechanical data**

Mating cycles	≥ 25
Engagement force	≤ 45 N*
Disengagement force	≥ 5 N
Retention force latch	≥ 110 N
Retention force primary lock	≥ 80 N
Retention force secondary lock	≥ 80 N
Coding efficiency	≥ 150 N

\* according to USCAR 25 Rev. 3 and the tests specified in USCAR 17 Rev.5 TG-G

**Environmental data**

Temperature range	-40°C to + 105°C
Thermal shock	ISO 20860-2 clause 9.2
Temperature and humidity	ISO 20860-2 clause 9.3
Vibration and mechanical shock	ISO 20860-2 clause 9.1
Dry heat	ISO 20860-2 clause 9.4
RoHS	compliant

- Limitations are possible due to the used cable type -

**Tooling**

Crimp dimension acc. to assembly instruction

Series tool:

Crimping applicator (AMK12A-102/90)	11WR023_A
Crimping applicator (AMK12A-102/22)	11WB015_A
Crimping applicator (AMK12A-102/40)	11WS002_A

Hand tool:

Crimping applicator	AMW007-SET
---------------------	------------

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG  
RF\_35/09.14/6.2

**Suitable cables**

Cable type

Dacar 462, Dacar 462-2, Dacar 140

**Packing**

Standard (optional)








N/A

Weight

3.9 g / pce

**Coding**

Part Number must be accomplished by codification

Coding	Color	RAL	Part-Number-RT
 A	black	sim. 9005	AMK12D-102Z5-A
 B	white	sim. 9010	AMK12D-102Z5-B
 C	blue	sim. 5012	AMK12D-102Z5-C
 D	bordeauxviolet	sim. 4004	AMK12D-102Z5-D
 E	green	sim. 6017	AMK12D-102Z5-E
 F	brown	sim. 8011	AMK12D-102Z5-F
 Z	waterblue	sim. 5021	AMK12D-102Z5-Z
	traffic purple	sim. 4006	secondary lock

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Pemwieser	01.03.16	T. Miedl	13.10.21	900	21-0885	L. Türk	13.10.21