

All dimensions are in mm

Interface

According to RN_108-04

Documents

PCB layout MB_604
Tape & Reel packaging tbd

Material and plating

Connector parts

Connector parts	Material
Center contact	Bronze
- Interface	
- PCB	
Outer contact (Interface)	Bronze
Outer contact (PCB)	Zinc alloy
Outer contact sheet	Bronze
Dielectric	LCP
Housing	HTN

Plating

Gold, min 0,15 µm over nickel
Tin, min. 0,5 µm, over nickel
Tin, min. 1.5 µm
Tin, min. 2 µm
Tin, min. 3 µm

Preliminary

Electrical data

Impedance	50 Ω
Frequency	DC to 9 GHz
Return loss	≥ 25 dB, DC to ≤ 3 GHz ≥ 20 dB, > 3 GHz to ≤ 6 GHz ≥ 12 dB, > 6 GHz to ≤ 9 GHz
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 15 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	≤ 800 V rms
Working voltage	≤ 60 V DC
Power current	≤ 1 A DC
Cross talk (optional)	≤ -60 dB up to 10 GHz

- Connector only, VSWR in application depends decisive on PCB layout -

Mechanical data

Mating cycles	≥ 25
Engagement force	≤ 45 N*
Disengagement force	≥ 5 N
Retention force latch	≥ 110 N
Coding efficiency	≥ 150 N

* according to USCAR 25 Rev. 3 and the tests specified in USCAR 17 Rev.5 TG-G

Environmental data

Temperature range	-40 °C to +105 °C
Thermal shock	ISO 20860-2 clause 9.2
Temperature and humidity	ISO 20860-2 clause 9.3
Vibration and mechanical shock	ISO 20860-2 clause 9.1
Dry heat	ISO 20860-2 clause 9.4
Soldering profile	acc. to IEC 60068-2-58; Group 3 (250 °C / 30 s)
RoHS	compliant

Packing

Standard	tbd pcs in tape & reel
Weight	7.63 g








Preliminary

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09_14/6.2

Coding

Part number has to be accomplished by codification

Coding		Color	RAL	Part-Number-RT
	A	black	sim. 9005	AMS2RD-40MZ5-A
	B	white	sim. 9010	AMS2RD-40MZ5-B
	C	blue	sim. 5012	AMS2RD-40MZ5-C
	D	claret violet	sim. 4004	AMS2RD-40MZ5-D
	E	green	sim. 6017	AMS2RD-40MZ5-E
	F	brown	sim. 8011	AMS2RD-40MZ5-F
	Z	waterblue	sim. 5021	AMS2RD-40MZ5-Z

Preliminary

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Mamou	30.04.19	F. Bachmeier	24.06.21	300	21-0885	L. Türk	24.06.21

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 3 / 3
--	--	--	--	--	--	--	---------------