

* tolerance results of backlash inner conductor - housing/secondary lock
 1) Dimensions can be used for incoming inspection

Interface

According to RN_084-01

Documents

Assembly instruction MA_HV0048

Material and plating

Connector parts

Power Contact
 Contact protection cap
 Housing
 Secondary lock
 Distance sleeve

Material

Copper
 PA10
 PA10 GF30
 PA10 GF30
 Brass

Plating / Color

Ag, min. 3µm, over Ni
 black
 black
 traffic purple
 Ni

Electrical data

Insulation resistance	≥ 200 MΩ / 1000 V_DC
Voltage class	B 60 V_DC < U ≤ 1500 V_DC 25 V_AC < U ≤ 1000 V_AC
Contact resistance (current)	≤ 0.4 mΩ
Design acc. To DIN EN 60664-1 (2008-1)	
Pollution grade	2
Type of isolation	Basic Isolation
Max. Altitude	5500m above sea level
Working voltage	1000 V_DC
Test voltage	3200 V_DC (at max. altitude 2000m above sea Level)
Rated surge voltage	2700 V_DC
Ampacity	depending on cross section of used cable connector side
EMI (shielding effectiveness)	70 dB (10 kHz - 5 MHz) 65 dB (5 MHz - 500 MHz)
High Voltage Interlock (HVIL)	No

Mechanical data

Mating cycles	≥ 50
Coding efficiency	≥ 300 N
IP class (mated)	depending on cross section of used cable connector side
IP class (unmated)	IPXXB
Vibration class	LV214 (2010-04) PG17-II (Random: DIN EN 60068-2-64) (Sinus: DIN EN 60068-2-6) (Shock: DIN EN 60068-2-27)

Environmental data

Temperature range	-40°C to +140°C
-------------------	-----------------

Application

Applicable for following connectors:

H4K134-W10016B1-YY	H4K135-W10016B1-YY	H4K136-W10016B1-YY	H4K137-W10016B1-YY
H4K134-W10025B1-YY	H4K135-W10025B1-YY	H4K136-W10025B1-YY	H4K137-W10025B1-YY
H4K134-W10035B1-YY	H4K135-W10035B1-YY	H4K136-W10035B1-YY	H4K137-W10035B1-YY
H4K134-W10050B1-YY	H4K135-W10050B1-YY	H4K136-W10050B1-YY	H4K137-W10050B1-YY

H4K134-W20016B1-YYY	H4K135-W20016B1-YYY	H4K136-W20016B1-YYY	H4K137-W20016B1-YYY
H4K134-W20025B1-YYY	H4K135-W20025B1-YYY	H4K136-W20025B1-YYY	H4K137-W20025B1-YYY
H4K134-W20035B1-YYY	H4K135-W20035B1-YYY	H4K136-W20035B1-YYY	H4K137-W20035B1-YYY
H4K134-W20050B1-YYY	H4K135-W20050B1-YYY	H4K136-W20050B1-YYY	H4K137-W20050B1-YYY

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05:10/6.2

Technical Data Sheet

Rosenberger

HPK

Device side



H4S115-92-000B-YY

Packing

Standard
Weight

20 pcs in box
64,94 g/pcs

Coding

Coding	Plug	Colour	RAL	Part-Number
BA		black	sim. 9004	H4S115-92-000B-BA
BC		black	sim. 9004	H4S115-92-000B-BC

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
L. Schneider	24.04.15	A. Koleber	12.02.18	300	17-0241	A. Kott	12.02.18

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Page
3 / 3