

All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to RN_103-01

Documents

Assembly instruction MA_HV0083
 Recommended install instruction MA_HV0089

Material and plating

Connector parts

Press in sleeve
 Press in ring
 Contact sleeve
 Coding

Material

Brass
 stainless Steel
 Brass
 PBT GB20

Plating

Ag, 0,5-2µm
 Ag, 3-6µm
 red (sim. RAL 3001) / black (sim. RAL 9005)

Application

Applicable for following connectors: H9S105-W1F070B1-Y, H9S105-W1F035B1-Y

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09_14/6.2

Technical Data Sheet

Rosenberger

DCS

**PRESS IN SLEEVE
ASSEMBLY**



H9K106-51-070B-Y

Packing

Standard
Weight

324 pcs. in box
39,8 g/pcs

Coding

Coding	Plug	Colour	RAL	Part-Number
A		red	sim. 3001	H9K106-51-070B-A
B		black	sim. 9005	H9K106-51-070B-B

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
R. Müller	10.07.15	F. Wein	22.03.18	a00	18-s135	R. Hochheim	22.03.18

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Page

2 / 2