



Main Features

- **Fast charge of two Batteries at the same time**
- **Portable design for ON-SITE use**
- **Powered by Alpha Site Analyzer DC Supply (IM-A-ACSRV-CHGR-BU)**
- **Smart Charge Function: LED light indicates battery status & charging progress**
- **Detection of defective battery packs**
- **Battery charging time:**
 - Typical: up to 90min. charging time can be up to 150min., depends on state of residual charge)

Contents

Battery Charger

General

Supply 100-240V
Dimensions 170x110x50 (LxWxH)
Weight 680g (1,5lb)

Environmental Data

Charging Temperature Range 0° to +50°C (depends on batteries)
Storage Temperature Range -30° to +60°C
Relative Humidity (non condensing) 5 to 95 %

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.
 All dimensions are in mm; tolerances according to ISO 2768 m-H

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
A.Maier	20.12.2018	A.Maier	13.01.2020	200	20-v017	C_Vitzthum	13.01.2020

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 84526 Tittmoning Germany www.rosenberger.de	Tel. : +49 8684 18-0 Email : info@rosenberger.de	Page 1 / 1
--	--	---------------

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG