



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

RPC-1.00 side according to IEC 61169-31
RPC-1.35 side according to IEC 61169-65

Documents

N/A

Material and plating

Connector parts

Center conductor
Outer conductor
Coupling nut
Dielectric

Material

CuBe
CuBe or equiv.
Stainless steel
PEEK

Plating

Gold, min. 1.27µm
Gold, min. 1.27µm
Passivated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

Adaptor
RPC-1.35 Plug – RPC-1.00 Plug

P9S101-S00D3

Electrical data

Frequency DC to 90 GHz
Return loss ≥ 28 dB, DC to 20 GHz
≥ 20 dB, 20 GHz to 40 GHz
≥ 17 dB, 40 GHz to 90 GHz

Mechanical data

	RPC-1.00	RPC-1.35
Mating cycles	≥ 500	≥ 3000
Maximum torque	0.70 Nm	1.65 Nm
Recommended torque	0.35 Nm	0.90 Nm
Gauge	0.000 mm to 0.030 mm	0.003 mm to 0.020 mm

Environmental data

Temperature range - 40 °C to +85 °C
RoHS compliant

Packing

Standard 1 pce in box
Weight 3.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	22.08.17	Markus Müller	17.12.19	e00	19-2422	Marion Striegler	17.12.19
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2