


1/2"
JUMPER

7-16 R/A MALE
7-16 R/A MALE

SLJ12SP-60R60R-X-00



Function Description

This part is a coaxial cable assembly for telecommunication equipment. It consists of 1/2" super flexible coaxial cable with PE jacket and two 7-16 r/a male connectors. The assembly is waterproof in mated condition and UV protected.

Available Variants

The assembly is available in lengths from 0.5 m to 10 m in intervals of 0.5 m. Different feet and inch lengths are available on request.

Assembly Parts

Connectors	7-16 r/a male connectors plated with white bronze
Cable	S-Link 1/2"S, PE jacket
Marking 1	Direct print onto the cable or on wrapping label Marking includes manufacturer, part nr. & batch no.
Marking 2	Direct print onto the cable or on wrapping label Marking includes "Rosenberger factory made" Position in the middle of the cable
Bend Protection	Molding material TPE compound or anti-kink sleeve

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

Technical Data Sheet

Rosenberger

1/2"
JUMPER

7-16 R/A MALE
7-16 R/A MALE

SLJ12SP-60R60R-X-00

Electrical Data

Impedance	50 Ω		
Frequency	DC to 3.8 GHz		
Return loss	L ≤ 10 m	L > 10 m	L > 20 m
380 – 470 MHz	≥ 30 dB	≥ 28 dB	≥ 26 dB
600 – 960 MHz	≥ 30 dB	≥ 28 dB	≥ 26 dB
1.4 – 2.7 GHz	≥ 26 dB	≥ 24 dB	≥ 22 dB
3.4 – 3.8 GHz	≥ 21 dB	≥ 19 dB	≥ 17 dB
Insertion loss typ.			
DC – 1 GHz	≤ 0.12 dB/m (cable) + 0.01 dB * √f (GHz)		
1 – 2.2 GHz	≤ 0.18 dB/m (cable) + 0.01 dB * √f (GHz)		
2.2 – 2.7 GHz	≤ 0.20 dB/m (cable) + 0.01 dB * √f (GHz)		
2.7 – 3.8 GHz	≤ 0.24 dB/m (cable) + 0.01 dB * √f (GHz)		
Intermodulation (3rd order @ 2 x 20 W)	typ.	max.	
	≤ -120 dBm	≤ -117 dBm	
Relative Velocity of Propagation	83 %		
DC breakdown voltage	2500 V		

Mechanical Data

Coupling torque (recommended)	25 to 30 Nm
Spanner flat on coupling nut	32 mm
Cable diameter, jacket	13.5 mm typ.
Tensile strength	700 N
Recommended hanger spacing	0.8 m
Minimum bend radius single	25 mm*
Minimum bend radius repeated	35 mm*

*Bending starts behind connector incl. the kink protection

Environmental Data

Operation temperature range	-40 °C to +80 °C
Installation temperature range	-25 °C to +60 °C
Degree of protection	IEC 60529, IP68 1 bar for 1 h (mated)
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Wimmer	20.12.2013	Chr. Janßen	15.10.2020	f00	20-1927	B. Wollitzer	15.10.2020
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2