



**Function description**

This part is a coaxial cable assembly for telecommunication equipment. It consists of 3/8" super flexible coaxial cable with FRNC jacket and two 4.3-10 male connectors. The assembly is waterproof in mated condition, fire retardant and UV protected.

**Available variants**

The assembly is available in lengths from 0.5 m to 10 m in intervals of 0.5 m. Different feet and inch lengths are available on request.

**Assembly parts**

Connectors	4.3-10 male (screw-type) connectors plated with white bronze
Cable	3/8" super flexible, FRNC jacket
Marking 1	Direct print onto the cable or on wrapping label Marking includes manufacturer, part nr. & batch no.
Marking 2	Direct print onto the cable or on wrapping label Marking includes "Rosenberger factory made" Position in the middle of the cable
Bend protection	Molding material PE compound with flame retardant

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

# Technical Data Sheet

# Rosenberger

3/8"  
JUMPER

4.3-10 MALE – 4.3-10 MALE

**SLJ38SF-64M64M-X-00**

## Electrical data

Impedance	50 Ω		
Frequency	DC to 3.8 GHz		
Return loss	L ≤ 10 m	L > 10 m	L > 20 m
380 – 470 MHz	≥ 30 dB	≥ 28 dB	≥ 26 dB
600 – 960 MHz	≥ 30 dB	≥ 28 dB	≥ 26 dB
1.4 – 2.7 GHz	≥ 26 dB	≥ 24 dB	≥ 22 dB
3.4 – 3.8 GHz	≥ 23 dB	≥ 21 dB	≥ 19 dB
Insertion loss typ.			
DC – 1 GHz	≤ 0.14 dB/m (cable) + 0.01 dB * √f (GHz)		
1 – 2.2 GHz	≤ 0.21 dB/m (cable) + 0.01 dB * √f (GHz)		
2.2 – 2.7 GHz	≤ 0.24 dB/m (cable) + 0.01 dB * √f (GHz)		
2.7 – 3.8 GHz	≤ 0.31 dB/m (cable) + 0.01 dB * √f (GHz)		
Intermodulation (3rd order @ 2 x 20 W)	typ.	max.	
	≤ -120 dBm	≤ -117 dBm	
Relative Velocity of Propagation	82 %		
DC Breakdown Voltage	2000V		

## Mechanical data

Coupling torque (recommended)	5 to 8 Nm
Spanner flat on coupling nut	22 mm
Cable diameter, jacket	10.2 mm typ.
Tensile strength	500 N
Recommended hanger spacing	0.6 m
Minimum bend radius single	13 mm*
Minimum bend radius repeated	25 mm*
*Bending starts behind connector incl. kink protection	

## Environmental data

Operation temperature range	-30 °C to +80 °C
Installation temperature range	-25 °C to +60 °C
Degree of protection	IEC 60529, IP68 1 bar for 1 h (mated)
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Wimmer	02.09.2014	F. Fraunhofer	13.05.2020	c00	20-1011	B. Wollitzer	13.05.2020
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2