



All dimensions are in mm; tolerances according to ISO 3302-1 M2

Description

In combination with the weather proofing kit SLWK112-C03 this component provides additional sealing for mated 7-16 connections with a threaded 7-16 long neck Antenna- or Radio port. It is UV protected.

Documents

Assembly instruction MA_SLWK112-C03_51

Material

Sealing: Oil Bleed Silicone

Mechanical data*

Mating cycles > 25

Environmental data*

Operation temperature range -40°C to +85°C
 Storage temperature range -40°C to +90°C
 Degree of protection* IEC 60529, IP68
 Water immersion IEC 60169-1, Sub-clause 14.7
 Termal shock IEC 60169-1, Sub-clause 16.4
 RoHS compliant

Weight

Weight 5 g / pce
 Packaging 10 pcs. In bag

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
J. Gramsamer	16/06/15	M. Wimmer	22.07.2015	a00	15-s265	Fl. Öllerer	22.07.2015

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de			Page 1 / 1
--	--	--	--	---	--	--	---------------