


All dimensions are in mm; tolerances according to ISO 3302-1 M2

Description

This weather proofing kit provides additional sealing for mated 7-16 connections. The sealing is pre installed on factory made jumpers and is UV protected.



Documents

Assembly instruction MA_SLWK112-C03

Material

Sealing: Oil Bleed Silicone

Mechanical data

Mating cycles > 25
 Suitable cable diameter 13 - 17 mm
 Suitable connector diameter 25 - 30 mm

Environmental data*

Operation temperature range -40°C to +85°C
 Storage temperature range -40°C to +90°C
 Degree of protection* IEC 60529, IP68
 Water immersion IEC 60169-1, Sub-clause 14.7
 Thermal shock IEC 60169-1, Sub-clause 16.4
 RoHS compliant

Weight

Weight 35 g / pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/06_10/1.0

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Wimmer	12.01.2015	M. Wimmer	22.07.2015	a00	15-s265	Fl. Öllerer	22.07.2015
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 1 / 1